

Technical data

Power supply: 12 V DC~28 V DC (Reverse power protection)

Input signal: K, E, S, B, J, T, R, N, etc
millivolt signal (-10mV~120mV)

Output signal: 4~20mA

Load resistance: $RL \leq [(U-12)/0.022]\Omega$; U is loop powered
voltafe

Range and Conversion accuracy list (25°C±2°C, not contain cold
junction compensation)

Type	Range		
K	-200°C~+1372°C	<300°C, ±0.3°C	≥300°C, ±0.1% F.S.
E	-100°C~+1000°C	<300°C, ±0.3°C	≥300°C, ±0.1% F.S.
J	-100°C~+1200°C	<300°C, ±0.3°C	≥300°C, ±0.1% F.S.
N	-200°C~+1300°C	<300°C, ±0.3°C	≥300°C, ±0.1% F.S.
S	-50°C~+1768°C	<500°C, ±0.5°C	≥500°C, ±0.1% F.S.
R	-50°C~+1768°C	<500°C, ±0.5°C	≥500°C, ±0.1% F.S.
T	-20°C~+400°C	<300°C, ±0.3°C	≥300°C, ±0.1% F.S.
B	+400°C~+1820°C	<500°C, ±0.5°C	≥500°C, ±0.1% F.S.
mv	-10mV~120mV	<10mV, 0.01mV	>10mV

S 0 Td <000F>Tj /T0 1 Tf 0.05 Tc -0.05 ET q 1% F

Compensation accuracy: 1°C (Temperature compensation range:
-40°C ~ +85°C)

Temperature drift: 50ppm/°C

Response time: ≤ 1s

Electromagnetic IEC 61326-1

compatibility:

Dielectric strength: ≥ 1500V AC (Input/Output)

Insulation resistance: ≥ 100MΩ (Input/Output)

Operation temperature: -40°C ~ +85°C

Storage temperature: -40°C ~ +85°C

Dimension: Ø 44×25.5mm

Wire size: 1.5mm²

Screw terminal torque: 0.5Nm