

→ 简介

4mA~20mA

→ 技术参数

C

: 12V DC~30V DC

(2 5):

0~60V AC; 0~110V AC; 0~220V AC
0~380V AC; 0~600V AC; 0~1000V AC

(7 8): 4mA~20mA

: $R_L \leq [(U-12)/0.022]\Omega$; U

: 0.2%F.S. (0~110%)

: 0.01%F.S./℃

: 40Hz~1kHz

: < 500ms

: 2

: EMC IEC 61326-3-1

(漏电流**1mA** 测试时间1分钟):

≥1500 V AC (/)

:


-20℃~+60℃

10%RH~90%RH (40℃)

80kPa~106kPa

-40℃~+80℃

代码	含义
1	0V~60V AC
2	0V~110V AC
3	0V~220V AC
4	0V~380V AC
5	0V~600V AC
6	0V~1000V AC
7	



Nanjing New Power Electric Co., Ltd.

B



IEC/EN 60664-1 2



IEC 61000-4

C



#c%"T '-r 2a~3 s& f2Qlg!) T 5r#c5H-^45f bTBC) ‡Ó •1%2•1%1u !a5 F€ Ue P hhE€‡8}0) ") " P P h ð q`% P hhE•i‡Ó •1%2•1%1u !a5 F€ XvSau &†„X 9‡Ó •1%2•1%1u !a5 F€ `5Dq P hhE•i‡Ó •1%2•1%1u !a5 tYfQw\$e



➔ 补充说明

